PRINTABLE MATERIAL
UV DIRECT TO FILM
TECHNICAL DATA SHEET

PRECISION LABELLING
POWERED BY RECOGNITION ID
IDENTIFY • MARK • COMPLY

Material *UV cured ink printed direct to substrate*

Thickness	.3mm overall after printing & laminating
Min. Single Label Size	40mm x 15mm
Max. Single Label Size	A2 / 420mm x 594mm

Durability

External Weathering	Can withstand direct exposure to weather Suitable for indoor installation
Chemical Resistance (ink only)	High resistance to isopropyl alcohol, mild acids & window cleaners. Vulnerable to strong acids & peroxides
Chemical Resistance (ink only)	Good resistance to mild chemicals, water and mild cleaning agents
Flexibility	Not suitable for substrates that require secondary bending or stretching

Installation *Dependant on selected substrate*

Adhesive Type	Direct to supplied substrate
Chemical Resistance (material only)	Resistant to common workplace contaminants and mild chemicals

Applications

- GPO Faceplates
- Switch Mechanisms
- Machine Nameplates
- Junction Boxes
- Electrical / Switchboard Enclosures
- Control Panels

Ordering

To request a quote or order this material, send us an email with item code **PL-DTF**, your details and the required label information.

Customer-supplied substrates remain the customer's responsibility for suitability, compliance, and fitness for purpose. Our responsibility is limited to the quality and performance of the printed UV-DTF transfer as applied to the supplied substrate. Chemical resistance data is provided as a guide only and is not exhaustive. End users are responsible for verifying suitability for their specific application.

Get In Touch

03 9898 8809 sales@precisionlabelling.com.au precisionlabelling.com.au

2/60-62 Abbott Road Hallam VIC 3803

Information contained in this specification sheet is accurate at the time of publication and is subject to change without notice. Product specifications, materials, manufacturing tolerances, and performance may vary due to application, environment, and production conditions. The end user is responsible for determining product suitability, intended use, installation requirements, and compliance obligations.
To the extent permitted by law, liability is limited for loss or damage resulting from incorrect selection, application, or use outside specified limitations.